



Physically-based modelling techniques for multisensory simulation

Nicolas Castagné

► To cite this version:

Nicolas Castagné. Physically-based modelling techniques for multisensory simulation. Enaction and enactive interfaces : a handbook of terms, Enactive Systems Books, pp.242-244, 2007. hal-00977742

HAL Id: hal-00977742

<https://hal.science/hal-00977742>

Submitted on 11 Apr 2014

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Physically-based modelling techniques for multisensory simulation

Nicolas Castagne [ACROE&INPG]

Contributors: Matthieu Evrard [ACROE&INPG]

Physically-based modelling techniques developed in parallel in computer graphics, computer music and virtual realities. Most of them are dedicated to a category of model depending on the synthesized phenomena: sound, movement, etc.

When one needs to build a multisensory scene (for example to be manipulated by using a force feedback transducer), most often, various exogenous models are used, one for each sensory modality. Models are then inter-related by some inter-control means, often asynchronous. As an example, in virtual realities, sound is most often simply obtained by triggering pre-recorded samples – and, eventually, processing them (e.g.: apply a spatialization algorithm) – when an event occurs in the visual scene.

The framework of enactive interfaces, however, emphasizes the unicity of human perception, and in parallel the need of a particularly high and thin correlation between the gesture of the user and the various multisensory stimuli generated. Indeed, implementing exogenous interconnected sound model, visual model, and sometimes haptic models, hardly enables the close interaction needed between the various stimuli feedback one needs. Making these models behave in a truly coherent manner in order to let the user believe that he perceives/manipulates an object is still a major difficulty.

Conversely, though it is still rarely done and difficult, one can also try to design a

single multisensory physically-based model. In such a case, as a vis-à-vis of the unicity of human sensori-motricity, the model is unique and generates all the sensory outputs in response to gesture in one shot. However, only a very few modelling frameworks qualify for such multisensory simulation. We review below the mass-interaction framework.

The Mass-interaction framework

Within the mass-interaction modular framework (also called particle modelling), a model is obtained by assembling, as a network, modules of two types: masses and physical linear and non-linear interactions. The technique differs from mass-spring meshes. It relates more to works like the pioneering [Greenspan, 73], or the more recent [Cadoz et al., 93] [Greenspan, 97] [Luciani et al., 91], since it consists in a specific algorithmic implementation of Newtonian mass-point physics. More precisely, differences include:

- It comes along with a number of linear and non-linear interactions (collisions, bow-like interaction, Newtonian interactions, friction interaction, plastic interaction...) instead of featuring only linear spring-dampers. In the models, the design of interaction is prominent.
- It promotes a constructivist, network-like, mesh-free, modelling process, rather than a mesh-discretization methodology. The physical modelling process starts from scratch. The designer assembles the basic modules as a network, by handling directly the mass-interaction formalism. No geometrical mesh of a volume or a surface needs to be a priori considered.

The mass-interaction technique is sometimes said to be quite expansive in terms of processing cost, and not to be very precise – we know, for example, that simulating wave propagation by using masses and interactions introduces some numerical bias as compared to the wave equation model. It is also considered as being unstable, in the sense that a

given model may diverge in certain configurations.

On the contrary, the technique is amongst the most modular. The basic masses and interactions are very elementary models of a piece of matter, that remain pertinent for the human senses (they all can be, for example, perceived through a haptic gesture device, or visually represented) and can be easily internalized by any user as representations of very basic objects. The technique is also robust since a stable network of masses and interactions behaves plausibly no matter how it was constructed. It thus enables a relevant mental model. The designer of the model is not required to refer to any continuous model of traditional physics, nor to consider the mass and spring network as a numerical analysis method. He often base his construction work on some intuition, trying to imitate or metaphorize the object he wants to model. Consequently, various modellers usable by the end-user have been introduced [Castagne & Cadoz, 02] [Evrard et al., 06] [Sod], etc.

Finally, the mass-interaction technique can be viewed as particularly generic. It has been successfully used in a large variety of applications in computer music, animation and virtual realities: sound resonator, wind and string instruments, bowed or plucked interaction, musical gesture generation, fluids, pastes, gels, sands, deformable objects, vehicles, dancing, etc.

Indeed, mass-interaction modelling applies to the modelling of any moving physical objects, particularly those in which the dynamics of the behaviour is prominent. So doing, it qualifies, as a unique feature, for the modelling of multisensory object and the building of enactive interfaces: a single model built within the mass-interaction framework, eventually multidimensional and multifrequency, may allow the synthesis at the same time of sounds, visual movements, and force-feedback data to be sensed through an haptic device, each of the phenomena being tightly correlated with each others.

References

- [Castagne & Cadoz, 02] Castagne, N, Cadoz, C: "GENESIS: A Friendly Musician-Oriented Environment for Mass-Interaction Physical Modeling". International Computer Music Conference, Sweden, 2002.
- [Cadoz et al., 93] Cadoz C., Luciani A. and Florens J. L.: "CORDIS-ANIMA: A Modeling and Simulation System for Sound and Image Synthesis - the General Formalism". Computer Music Journal 17(4), 1993.
- [Evrard et al., 06] Matthieu Evrard, Annie Luciani, Nicolas Castagné, MIMESIS: Interactive Interface for Mass-Interaction Modeling, In Proceedings of CASA 2006, Geneva, July 2006, Nadia Magnenat-Thalmann & al. editors. pp177-186.
- [Greenspan, 73] D. Greenspan. Discrete Models. Applied Mathematics Collection. Addison-Wesley (1973).
- [Greenspan, 97] D. Greenspan. Particle Modeling. Birkhauser Ed (1997).
- [Luciani et al., 91] A. Luciani, S. Jimenez, J.-L. Florens, C. Cadoz, O. Raoult. Computational physics: a modeler simulator for animated physical objects. Proceedings of the European Computer Graphics Conference and Exhibition. Eurographics'91, pp 425-436, Vienna, Austria, Elsevier Ed, Sep. 1991.
- [Sod] Sodaplay java applet - <http://www.sodaplay.com>

Related items

Believability_1&2
 Haptic rendering of virtual objects
 Mapping and control vs. instrumental interaction
 Multimodality and enaction